

## EPS® 2103

### All-Acrylic Emulsion

#### MARKET SEGMENT: CONSTRUCTION

#### COMMON APPLICATIONS: EIFS Basecoat, EIFS Finish Coat, Concrete Admixture

For EIFS (exterior insulated finishing system) applications, EPS® 2103 is an excellent choice to use as a modifier/additive for cementitious base coats and as the binder for finish coats. For concrete admixture applications, EPS® 2103 imparts increased flexibility and decreased permeability to the system.

#### PERFORMANCE BENEFITS

- Dirt pickup resistance (DPUR)
- Water resistance
- Yellowing and chalking resistance
- Color fastness
- Alkali stability
- Reduces permeability of cement matrices
- Improves flow of cement-based systems
- Increases strength, flexibility and durability
- Low odor

#### TYPICAL PROPERTIES

<b>Weight Solids</b>	46.5 ± 0.7%
<b>Weight/Gallon</b>	8.80 ± 0.10
<b>pH</b>	8.5 - 9.5
<b>Volume Solids</b>	43.50 ± 0.7%
<b>MFFT</b>	5-9° C

These typical properties do not represent specifications.

#### SUGGESTED FORMULATIONS

- EPS® 2103 EIFS Base Coat Formulation
- EPS® 2103 EIFS Finish Coat Formulation
- EPS® 2103 EIFS Premium Finish Coat Formulation